



# OK



## The Power of Fastening

# Wood

## OK Fuel Cells for Wood-Application

Temperature Range: From -15°C up to 50°C  
Packaging: 72 pcs (6 x 12 Fuel Cells)

Minimum Order Quantity: 2.880 pcs

Type	Part-No.	Size	Gas Amount	Capacity	For Nailers
Fuel Cell OK 31,5x165 R High Pressure	220016	31,5 x 165 mm	40 g	more than 1.100 shots	Dynamik D90 NR90GC IM350/90 CT IM PPN5
Fuel Cell OK 31,5x80 Y High Pressure	220047	31,5 x 80 mm	18 g	more than 1.000 shots	IM65 IM 250
Fuel Cell OK 31,5x165 Super Fuel	220092	31,5 x 165 mm	40 g	more than 1.100 shots	

### Certified High Pressure Fuel Cells for Europe according to DIN EN 12205

- High pressure fuel cell with approved can and approved valve  
➔ safe for the end-user!
- Improved and clean high-performance gas
- Full function from -15°C up to +50°C



# Concrete / Steel

## OK Fuel Cells for Concrete-/Steel-Application

Packaging: 72 pcs (6 x 12 Fuel Cells)

Minimum Order Quantity: 2.880 pcs

Type	Part-No.	Size	Gas Amount	Capacity	For Nailers
Fuel Cell OK 31,5x152 R CN60/P1000	220023	31,5 x 152 mm	40 g	more than 1.000 shots	OK CN60 Pulsa 1000
Fuel Cell OK 31,5x115 P700	220030	31,5 x 115 mm	25 g	more than 700 shots	Pulsa 700E/P

### OK Packs - OK Fuel Cells + Nails for CN60/P1000

Packaging Unit: each with 1.000 nails and one fuel cell for CN60 / Pulsa 1000.

Standard-Nails			Premium-Nails		
Nail-length	Type	Part-No.	Nail-length	Type	Part-No.
15 mm	Pack OK 15 CN60/P1000	220160	15 mm	Pack OK 15 Premium P1000/CN60	220221
20 mm	Pack OK 20 CN60/P1000	220177	17 mm	Pack OK 17 Premium P1000/CN60	220238
25 mm	Pack OK 25 CN60/P1000	220184	19 mm	Pack OK 19 Premium P1000/CN60	220245
30 mm	Pack OK 30 CN60/P1000	220191	22 mm	Pack OK 22 Premium P1000/CN60	220252
35 mm	Pack OK 35 CN60/P1000	220207	27 mm	Pack OK 27 Premium P1000/CN60	220269
40 mm	Pack OK 40 CN60/P1000	220214	32 mm	Pack OK 32 Premium P1000/CN60	220276
50 mm	Pack OK 50 CN60	220283			
58 mm	Pack OK 58 CN60	220290			
20 mm	Pack OK M6-20 CN60	220313			

### OK Packs - OK Fuel Cells + Nails for P700

Packaging Unit: each with 1.000 nails and one fuel cell for Pulsa 700.

Standard-Nails			Premium-Nails		
Nail-length	Type	Part-No.	Nail-length	Type	Part-No.
15 mm	Pack OK 15 P700	220108	15 mm	Pack OK 15 Premium P700	220320
20 mm	Pack OK 20 P700	220115	17 mm	Pack OK 17 Premium P700	220337
25 mm	Pack OK 25 P700	220122	19 mm	Pack OK 19 Premium P700	220344
30 mm	Pack OK 30 P700	220139	22 mm	Pack OK 22 Premium P700	220351
35 mm	Pack OK 35 P700	220146	27 mm	Pack OK 27 Premium P700	220368
40 mm	Pack OK 40 P700	220153	32 mm	Pack OK 32 Premium P700	220375

### Nailer OK CN 60 for Concrete-/Steel-Application

Part-No.	220504	Capacity Fuel Cell	at least 1.000 shots
Power	85 Joule	Capacity Battery	up to 6.000 shots
Weight	3,7 kg	Capacity Magazine	max. 40 nails
Length	390 mm	Tool Speed	2-3 shots per sec.
Width	118 mm	Nail Size	15 mm - 58 mm
Height	450 mm	Emission Sound Pressure LpA <sub>1m,d</sub>	96 dB



## OK Befestigung GmbH & Co. KG

Office: Liesentorweg 19a, D-47802 Krefeld  
Production/Warehouse: Am Selder 35a, D-47906 Kempen  
Managing Director: Dr. Olaf Kersten  
HRA 5083, Amtsgericht Krefeld

Tel.: +49-(0)2151-953639  
Fax: +49-(0)2151-953649  
E-Mail: [vertrieb@okbefestigung.de](mailto:vertrieb@okbefestigung.de)  
[www.okbefestigung.de](http://www.okbefestigung.de)